


EL-G16E2G-POE

L2 POE+ 스위치



EL-G16E2G-POE는 기가비트 이더넷 POE 16포트를 다운링크로 제공하고 기가비트 SFP 2포트를 업링크로 제공하는 L2 POE 스위치입니다.

Feature

- o 10/100/1000Base-T PoE * 16, 100/1000 Base-X * 2, Console * 1
- o 36G Switching Capacity
- o IEEE802.3af/at (POE, POE+) 지원
- o IEEE802.3x Flow Control 지원
- o Static routing, IGMP Snooping, DHCP relay 지원
- o Flow classification based on L2/L3 802.1P/DSCP priority re-labeling, SP, WRR and SP+WRR, Flow monitoring and flow shaping QoS 지원
- o IEEE 802.1D/1s/1w의 STP/RSTP/MSTP를 지원
- o Console, Telnet, SSH2.0, WEB Management, SNMP v1/v2/v3

Application


- o CCTV, ITV and Traffic control system
- o Campus Network
- o Community Network
- o Security system
- o Process control and monitoring system

Specification

Standard	IEEE802.3i 10Base-T IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X
Fixed port	10/100/1000M Base-T PoE * 16 100/1000 Base-X SFP * 2 Console * 1
POE Port	Port 1-16 can support IEEE 802.3af/at
Switching Capacity	36Gbps
Forwarding Rate	26.78Mpps
FLASH / RAM	32MB /128MB
Jumbo frame	9.6K
MAC table	8K
L3	Static route for IPv4 and IPv6
VLAN	port based VLAN (4K) protocol based VLAN IEEE802.1Q, QinQ
Port Aggregation	LACP
Storm control	Broadcast / Unicast / Multicast
Spanning tree	STP(IEEE802.1d) RSTP(IEEE802.1w) MSTP(IEEE802.1s)
Multicast	IGMP Snooping V2/v3 MLD Snooping V1/V2
DHCP	DHCP server/relay/client DHCP snooping
QoS	Each port supports 8 output queues MAC/IP/TCP/UDP/VLAN/COS/DSCP/TOS based QoS 802.1P/DSCP priority re-labeling scheduling mechanism (SP, WRR, SP+WRR) flow monitoring and traffic shaping
ACL	L2 to L4 packet filtering function ACL based on port and VLAN
Security	Port isolation Port security IP source guard IEEE 802.1x AAA & Radius MAC learning limit ARP inspection

Management	Console, Telnet, SSH v1/v2, Web, SNMP v1/v2/v3 , TFTP
PoE Standard	IEEE802.3af/at
Power Supply Pin	Default: 1/2(+),3/6(-)
Max Power Per Port	30W
Total PWR / Input Voltage	400W (AC100-220V)
Size	440*290*44.5mm(W*D*H)
Power	AC100~240VAC (auto-adaptable), 50-60Hz
Environment	Working temperature: -20-55℃ Storage temperature: -40-75℃ Humidity: 5-90% non condensing

Dimension



4F, 2-dong,234, Saneop-ro 155beon-gil, Gwonseon-gu, Suwon-si, Gyeonggi-do, Republic of Korea
Tel : 031-257-7157 / Fax : 031-257-7159

E-mail : elimopt@elimopt.co.kr / Web : <http://www.elimopt.co.kr/>